



Rackmount LCD monitor
机柜型

TLS560HD-3

TLS560HD-3/ TLS560SD-3/ TLS560NP-3

规格参数

屏幕尺寸	5.6"
像素	640 (H) × 480 (V)
点距	0.0588 (H) × 0.1764 (V) mm
显示比例	4:3 / 16:9 可转换
亮度	350cd/m ²
对比度	500:1
响应时间	10 ms
可视角度	左右 140° / 上下 120°
输入电压	DC 12V
功率消耗	≤27W
外观尺寸	L 432 × H 132 × D 87.1 mm
安装尺寸	L 482.6 × H 132 × D 87.1 mm (≤3U)
重量	3.1 kg

输入格式及功能

功能	型号	TLS560HD-3	TLS560SD-3	TLS560NP-3	备注
视频输入	复合视频	●	●	●	BNC 1路 × 3
	分量 (Y/Pb/Pr)	●	●	●	BNC 1路 × 3
	SD-SDI	●	●		BNC 1路 × 3
	HD-SDI	●			BNC 1路 × 3
	音频输入	●	●	●	RCA 1路 × 3 (双声道)
视频输出	音频监听	●	●	●	扬声器 2 × 0.5W (8Ω) + 耳机
	SDI 嵌入音频	●	●		PPM / UV
	复合视频	●	●	●	BNC 1路 × 3
	分量 (Y/Pb/Pr)	●	●	●	BNC 1路 × 3
	SD-SDI	●	●		BNC 1路 × 3
TALLY 显示	HD-SDI	●			BNC 1路 × 3
	TALLY 显示	●	●	●	红 / 绿双色



配件



交流电源适配器
(标配)



交流电源线
(标配)



SDI视频线
(标配)



TALLY插头
(标配)